

group PUT method

Create a new group.

If no errors are returned, the response is the same as [the group GET method](#); obviously no numbers will be listed since it will be an empty group.

Specific errors:

Code	Meaning
0	DEPRECATED – status code 400 (bad request) is returned instead.
1	A group with that name already exists (group names are not case-sensitive).
2	The group name is invalid. Only up to 25 alpha-numeric characters, and '-' are allowed. The name cannot consist of only digits, at least one alpha character or '-' must be present.

that a 404 status code is returned if the group specified does not exist; 400 is returned if the group name was not specified.

DTD:

```
<?xml version="1.0" encoding="UTF-8"?>
<!--
  PUBLIC ID : -//textmarketer.co.uk//DTD Web Services
  REST 1.6//EN
  SYSTEM ID :
  http://api.textmarketer.co.uk/services/rest/DTD/group_get.dtd
-->
<!--ELEMENT response (group)>
<!--ATTLIST response
  processed_date CDATA #REQUIRED
>
<!--ELEMENT group (number*) >
<!--ATTLIST group
  name CDATA #REQUIRED
  numbers CDATA #REQUIRED
  id CDATA #REQUIRED
  is_stop CDATA #REQUIRED
>
<!--ELEMENT number (#PCDATA) >
```

Next: [The groups resource](#)

Home: [All Documentation](#)