groups GET method

Get a list of available 'send groups' – pre-defned groups containing a list of mobile numbers to send a message to. Also lists 'stop groups' – numbers in these groups will never be sent messages to. Every account has at least one stop group, so that your recipients can always opt out of receiving messages from you. This is a legal requirement.

Example successful response body XML:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE response PUBLIC
"-//textmarketer.co.uk//DTD Web Services REST
1.6//EN""http://api.textmarketer.co.uk/services/rest/DTD
/groups_get.dtd">
<response processed_date="2011-04-14T16:32:40+01:00">
 <groups quantity="2" >
  <group name="short_ZDZY" numbers="0" id="56"
is_stop="true"/>
  <group name="mygroup" numbers="0" id="78"
is_stop="false"/>
 </groups>
</response>
```

Response meanings:

XML tag/attribute	Meaning
groups	Contains a list of available groups.
quantity	The number of groups available.
group	Details of the group.
name	The name of the group.
id	The unique ID of the group.
is_stop	Whether or not this is a 'stop group' – true/false.
numbers	The quantity of numbers present in the group.

Specific errors: None.

DTD for groups GET:

```
<?xml version="1.0" encoding="UTF-8"?>
<!--
  PUBLIC ID : -//textmarketer.co.uk//DTD Web Services
REST 1.6//EN
  SYSTEM ID :
http://api.textmarketer.co.uk/services/rest/DTD/groups_g
et.dtd
-->
<!ELEMENT response (groups)>
<!ATTLIST response
  processed_date CDATA #REQUIRED
>
<!ELEMENT groups (group*)>
<!ATTLIST groups
 quantity CDATA #REQUIRED
>
<!ELEMENT group (#PCDATA) >
<!ATTLIST group
  name CDATA #REQUIRED
  numbers CDATA #REQUIRED
  id CDATA #REQUIRED
  is_stop CDATA #REQUIRED
>
```

Next: The keywords resource

Home: All Documentation