# addNumbersToGroupWithName

Add a number/numbers to a 'send' group (excluding 'merge' groups).

# Example

```
$add=$tmClient->addNumbersToGroupWithName(array('447000000001','447000000002'), 'My
Group');
if (!empty($add['added']))
{
    echo count($add['added'])." numbers were successfully added:<br/>\n";
    foreach ($add['added'] as $number)
    echo "$number <br/>\n";
}
```

Name (or integer ID) of the group to add the numbers to.

### Arguments:

array **\$numbersArray**: An array of the MSISDNs (mobile number(s)) you wish to add.

# string/int \$groupName:

#### Returns:

an array with 3 keys: 'added', 'stopped', 'duplicates', each corresponding value being an array of numbers

Array key	Value
added	Array. An array of numbers in international format (e.g.447000000000 for a UK mobile). These numbers were successfully added to the group.
stopped	Array. An array of numbers in international format. These numbers were not added to the group because they are in a 'stop' group.
duplicates	Array. An array of numbers in international format. These numbers were not added to the group because they are already in the group.

## Specific error codes:

Code	Meaning
0	The group ID or name was not specified or was invalid.
2	No numbers were supplied for adding to the group.
3	A number was not of a valid format.
4	This service will not add to a merge group. Merge groups are not handled by this function.

error code 404 is reported if the group does not exist. See General error codes

Next: createSubAcco

unt

Home: Developers
 Documentation

You must know! Our example code is an illustration of how you might integrate with our systems and is not certified for production environments. You are responsible for testing and QA.